




## 13 inch touchscreen

Item number: 13TS7

This Full HD 13 inch touchscreen has a reliable multi-touch panel which ensures accurate operation. The 13TS7 provides crystal-clear image quality with excellent 178° viewing angles and is compatible with Windows, Mac, Linux & Android operating systems. The touchscreen monitor is designed for professional applications and suitable for intensive use.

- ✓ Full HD multi-touch panel
- ✓ Windows, Mac, Linux & Android compatible
- ✓ Desktop and wall mountable
- ✓ 319 x 200 x 33 mm



**GENERAL**

Manufacturer	Beetronics
Item number	13TS3
Product name	13 inch touchscreen
Warranty	2 years

**SUPPORTED OPERATING SYSTEMS**

Windows	(Windows 8, 10)
Windows Embedded	(Windows embedded 8, 10)
macOS	(Sierra, High Sierra, Mojave, Catalina, Big Sur)
Linux	✓
Chrome OS	✓
Brightsign	✓
Android	(Android PC or Mediabox - Android 6.0 and higher - not compatible with smartphones or tablets)
Drivers	No drivers needed. Plug & Play

PANEL	
Type	LED-IPS
Diagonal size	13.3 inches (338 mm)
Aspect ratio	16:9 (4:3 adjustable)
Native resolution	1920 x 1080
Supported resolutions	1920 x 1080 (max), 640 x 480 (min)
Pixels per inch	165 PPI
Viewing angle	178° horizontal, 178° vertical
Colour encoding system	PAL/NTSC/SECAM
Brightness	400 cd/m2
Contrast	1000:1
Touch technology	Capacitive, 10-point multitouch (PCAP)
Control	Stylus, hand, glove

CONNECTIVITY	
HDMI	✓ 1x
VGA	✓ 1x
BNC (CVBS)	✓ 1x
RCA video	✓ 1x
AUX output	✓ 1x
USB	✓ Only for touchscreen functionality

**SIZE & WEIGHT**

Colour	Black
Weight	890 gram (1310 gram with stand)
Width	319 mm
Height	200 mm (+0 to 37 mm with stand)
Thickness	33 mm
Display dimensions	305 x 188 mm

**FEATURES AND FUNCTIONS**

Audio	Integrated speakers
Key-lock	The control buttons can be blocked
Auto-on	Automatically powers on when it receives current or a signal
Dimmable	Adjustable backlight brightness
Mirroring	Image can be mirrored, horizontally and vertically

**POWER**

Input voltage	DC 12V
Power supply	Input: 110-240V ~ 50/60Hz - Output: 12V-2A
Consumption	<15 Watt (0.5 Watt standby)

#### ENVIRONMENTAL

Operating temperature	-20°C to +60°C
Storage temperature	-20°C to +70°C
Operating humidity	20% - 90% non-condensing

#### MOUNTING

Wall mount	✓ VESA (75 mm)
Flush mount	✓ Possible, no accessories available
Stand	✓ Adjustable and detachable

#### CERTIFICATIONS & STANDARDS

IP rating	IP65 front panel
Certifications	CE, FCC, RoHS, REACH

#### PACKAGE CONTENT

Includes	Touchscreen, Mains adaptor, Remote control, USB cable, Stand, Manual
----------	--





