



Anybus X-gateway – EtherNet/IP Adapter- EtherNet/IP Adapter

The Anybus X-gateway allows you to seamlessly inter-connect/extend PLC control systems and their connected devices on an EtherNet/IP network.

FAST COPYING OF I/O DATA

The X-gateways primary function is with the fast transfer of cyclic I/O data between the two networks. This offloads your PLC from working with additional calculations. The gateway acts as an Adapter on both sides and provides a simple network extension. The data transmission is completely transparent with a maximum data capacity of 512 bytes in each direction.

EASY CONFIGURATION - NO PROGRAMMING REQUIRED!

The connection between the two networks is quickly set up in the Anybus Configuration Manager software, included with the X-gateway. No programming skills are needed to set up the X-gateway. As factory default the X-gateways have a pre-defined I/O size of 20 bytes I/O.



Features and benefits

- Fast copying of cyclic I/O data between the two EtherNet/IP networks (10-15 ms)
- Proven and tested with all PLC manufacturers
- Supports up to a maximum of 512 bytes of Input and Output data in each direction
- Possibility to build web pages displaying and controlling a factory floor process with data from the other connected network
- Fast, dynamic transfer of fieldbus data to e.g. SCADA/HMI/Enterprise level systems based on Microsoft Windows, via the included Anybus OPC server
- Optional control status information added to I/O data for diagnostic purposes
- Robust stand-alone housing for use in harsh industrial environments
- Global free technical support and consultancy

EtherNet/IP Adapter/Slave interface

EtherNet/IP adapter settings can be made either via the built-in web interface, or by importing the provided .EDS file into engineering tool of the controlling PLC.

- EtherNet/IP CONFORMANCE TESTED™ by ODVA
- EtherNet/IP Level 2 I/O Server CIP
- 10/100Mbit operation in full or half-duplex
- Max. 509 bytes Input and 505 bytes Output data
- Device Level Ring (DLR) functionality available (announce-based ring participant)
- Integrated FTP server provides easy file management using standard FTP clients.
- Web server with dynamic data capability and Server Side Include (SSI) capability
- Email client with dynamic data capability and Event-triggered email handling

- Per-user security framework
- Quality of Service (QoS) available
- DNS Capability
- TCP/IP settings via DHCP/ARP/Anybus IPconfig (HICP)
- Integrated switch allowing for a daisy-chain topology
- 2x RJ-45 EtherNet/IP ports available simultaneously

EtherNet/IP Adapter/Slave interface

EtherNet/IP adapter settings can be made either via the built-in web interface, or by importing the provided .EDS file into engineering tool of the controlling PLC.

- EtherNet/IP CONFORMANCE TESTED™ by ODVA
- EtherNet/IP Level 2 I/O Server CIP
- 10/100Mbit operation in full or half-duplex
- Max. 509 bytes Input and 505 bytes Output data
- Device Level Ring (DLR) functionality available (announce-based ring participant)
- Integrated FTP server provides easy file management using standard FTP clients.
- Web server with dynamic data capability and Server Side Include (SSI) capability
- Email client with dynamic data capability and Event-triggered email handling
- Per-user security framework
- Quality of Service (QoS) available
- DNS Capability
- TCP/IP settings via DHCP/ARP/Anybus IPconfig (HICP)
- Integrated switch allowing for a daisy-chain topology
- 2x RJ-45 EtherNet/IP ports available simultaneously

TECHNICAL SPECIFICATIONS

Dimensions (L•W•H)	114 x 44 x 127mm or 4,49 x 1,73 x 5,00"
Weight	400g or 0,880 lbs
Operating temperature	-25 to +65 °C or -13 to +149 °F
Storage temperature	-40 to +85 °C or -40 to +185 °F
Power supply	24 VDC +/- 20% via 2-pole 5.08 mm Phoenix pluggable screw connector
Current consumption	max. 400mA (Typical 200mA)
Enclosure material	Aluminium and plastic
Installation position	Vertical / Flat*
Galvanic isolation	YES, on both BUS/Ethernet side
Mechanical rating	IP20, NEMA rating 1
Mounting	DIN-rail (EN 50022 standard)
I/O configuration	via USB port with Anybus Configuration Manager software
Certifications	CE, CULUS, RoHS

File	Version	Size	Read online
------	---------	------	-------------

Ordering information

Order Code	AB7831
Included components	Gateway Quick start documentation USB configuration cable Power supply not included Configuration and Anybus OPC server software is available for download.

3 year guarantee. For purchasing instructions and terms and conditions, see: [How to buy](#).

Copyright © 2020 HMS Industrial Networks - All rights reserved.