

Q.raxx slimline RS A106 -8

Measurement Module for Strain Gage and LVDT/RVDT


Q.raxx slimline RS is Q.series' highest density 19" 1U rackmount DAQ system - the ideal solution for boom box installations or applications that require maximum channel density and custom sensor terminations. Q.raxx slimline RS DAQ systems utilize an external high-performance controller for communication, control, and data logging purposes. Multiple systems can be synchronized to each other allowing for efficient DAQ distribution with low jitter and gradual expansion up to thousands of channels. In addition to available variations, the Q.raxx slimline RS is fully customizable to your specific measurement needs.

- RS485 fieldbus interface up to 24 Mbps
- Power supply 10 up to 30 VDC
- Rack standard, 1 high unit (1 HU)
- Connectable to any Controller, e. g. Q.gate or Q.pac



Key Features


- **8 Analog input channels**
strain gauge and inductive half and full bridges, LVDT, RVDT quarter bridge with completion terminal
- **DC and carrier frequency (CF) principle**
2.5 and 5 VDC excitation, 2.5 and 5 VDCeff excitation carrier frequency, 600 Hz or 4.8 kHz configurable per channel
- **8 Analog output channels**
±10 VDC, 10 kHz update rate per channel
- **High-accuracy digitization**
24-bit ADC, 10 kHz sample rate per channel
- **4 digital I/Os**
input: state, tare, memory reset, output: state, alarm, threshold
- **16 Digital inputs or outputs**
status, trigger, tare, alarm, command
- **Signal conditioning**
linearization, filtering, average, scaling, min/max, RMS, arithmetic, alarm
- **3-Way galvanic isolation**
Channel to channel, channel to power supply, and channel to bus



Q.raxx slimline RS A106 -8


Measurement Module for Strain Gage and LVDT/RVDT

Block diagram



Technical Data

Terminal assignment 10pole screw



Analog Input Slimline

Channels	8
Accuracy	0.02 % typical 0.05 % in controlled environment ¹ 0.1 % in industrial area ²
Linearity error	0.02 % typical full-scale
Repeatability	0.01 % typical (within 24 hrs)
Input impedance	>10 MΩ
Isolation voltage	500 VDC channel to channel, to power supply, channel to bus ³

¹ according to EN 61326 2006: appendix B

² according to EN 61326 2006: appendix A

³ noise pulses up to 1000 VDC, continuous up to 250 VDC

Q.raxx slimline RS A106 -8

Measurement Module for Strain Gage and LVDT/RVDT

Strain Gage Measurement

Bridge configuration(s)	resistive full-bridge (4/6-wire) resistive half-bridge (3/5-wire) resistive quarter-bridge 120 Ω or 350 Ω (3-wire, with bridge completion terminal)			
Allowable sensor cable length	< 30 m			
Shunt resistor	100 kΩ internal resistor			
Bridge excitation	2.5 - 5 VDC 2.5 - 5 Veff (Carrier Frequency)			
Bridge excitation stability	< 0.01% / 24 hrs			
Bridge excitation drift	< 0.02% / 10 K			
	5 VDC	5 Veff (CF)	2.5 VDC	2.5 Veff (CF)
Allowable sensor resistance	> 300 Ω	> 300 Ω	> 100 Ω	> 100 Ω
Input range	±1.25 mV/V	±1.25 mV/V	±2.5 mV/V	±2.5 mV/V
	±2.5 mV/V	±2.5 mV/V	±5 mV/V	±5 mV/V
	±25 mV/V	±25 mV/V	±50 mV/V	±50 mV/V
	±50 mV/V	±50 mV/V	±100 mV/V	±100 mV/V
	±100 mV/V	±100 mV/V	±200 mV/V	±200 mV/V
	±200 mV/V	±200 mV/V	±400 mV/V	±400 mV/V
	±500 mV/V	±500 mV/V	±1000 mV/V	±1000 mV/V
Long-term stability	< 0.2 μV/V / 24 hrs (DC excitation) < 0.1 μV/V / 24 hrs (CF excitation)		< 2 μV/V / 8000 hrs (DC excitation) < 1 μV/V / 8000 hrs (CF excitation)	
Temperature drift (range 2.5 mV/V)	< 0.2 μV/V / 10 K Offset drift		< 0.05 % / 10 K Gain drift	
Noise (range 2.5 mV/V)	0.3 μV/V at 0 up to 10 Hz		1 μV/V at 10 up to 1 kHz	

LVDT/RVDT Measurement

Sensor connection	4- / 6-wire	
Sensor excitation (selectable)	5 Veff	2.5 Veff
Allowable sensor resistance	> 300 Ω	> 100 Ω
Input range	±1.25 mV/V	±2.5 mV/V
	±2.5 mV/V	±5 mV/V
	±25 mV/V	±50 mV/V
	±50 mV/V	±100 mV/V
	±100 mV/V	±200 mV/V
	±200 mV/V	±400 mV/V
	±500 mV/V	±1000 mV/V
Allowable sensor cable length	< 100 m ¹	
Long-term stability	< 0.1 μV/V / 24 hrs	< 1 μV/V / 8000 hrs
Temperature drift (range 2.5 mV/V)	< 0.2 μV/V / 10 K Offset drift	< 0.05 % / 10 K Gain drift
Signal-to-noise ratio	< 0.3 μV/V at 10 Hz	< 1 μV/V at 100 Hz

¹ low capacity sensor cable is strongly recommended

Q.raxx slimline RS A106 -8

Measurement Module for Strain Gage and LVDT/RVDT

Analog Output

Channels	2	
Accuracy	0.02 % typical	
Voltage output	±10 VDC	
Allowable load resistance	>2 kΩ	
Long-term drift	<1 mV / 24 hrs	<2.5 mV / 8000 hrs
Temperature drift	<1 mV / 10 K Offset drift	<0.05 % / 10 K Gain drift
Noise voltage	<2 mV at 10 Hz	<10 mV at 1 kHz

Digital Input & Output

Channels	4 configurable I/Os	
Mode(s) of operation	status	
Logic voltage	<2 VDC (Low) >10 VDC (High)	
Input type	PNP (current sinking)	
Input voltage	30 VDC max.	
Output voltage	10 to 30 VDC (external supply required)	
Contact	open drain p-channel MOSFET	
Load capacity	30 VDC / 100 mA (ohmic load)	

Analog to Digital Conversion

Resolution	24-bit	
Sample rate	10 kHz per channel	
Modulation method	sigma-delta	
Anti-aliasing filter	2 kHz, 3rd order (DC excitation) 1 kHz, 3rd order (4.8 kHz CF excitation) 100 Hz, 3rd order (600 Hz CF excitation)	
Digital filters	Infinite impulse response (IIR), low-pass, high-pass, band-pass, band-stop, to 8th order Butterworth or Bessel, frequency range 0.1 Hz to 1 kHz in steps of 0.1 (adjustable via software)	
Averaging	configurable or automatic according to the user-defined data rate	

Digital to Analog Conversion

Resolution	16-bit	
Update rate	10 kHz per channel	
Settling time	3 μs	

Communication Interface

Protocols	proprietary Localbus (115200 bps to 24 Mbps, latency <100 ns) ASCII (19200 bps to 115200 bps) Modbus RTU Profibus-DP (19200 bps to 12 Mbps) (special Firmware required)	
Data format	8E1	
Electrical standard	ANSI/TIA/EIA-485-A, 2-wire	

Q.raxx slimline RS A106 -8

Measurement Module for Strain Gage and LVDT/RVDT

Power Supply

Input voltage	10 to 30 VDC, overvoltage and overcurrent protection
Power consumption	2.5 W (approx.)
Input voltage influence	<0.001 % / V

Environmental Specifications

Electromagnetic compatibility (EMC)	according to IEC 61000-4 and EN 55011
Operating temperature	-20°C to +60°C
Storage temperature	-40°C to +85°C
Relative humidity	5 - 95 % at 50°C (non-condensing)

Remarks

Are subject to a warm-up period of at least 45 minutes

in a controlled electromagnetic environment¹

With configuration: Low-pass 10Hz²

Specifications subject to change without notice

¹ according to EN 61326 2006: appendix B

² according to EN 61326 2006: appendix A

Mechanical information

Type	19" Standard, 1 Unit
Measurements (W x H x D)	444 x 44 x 260 mm
Weight	approx. 2000 g

Ordering Information

Article number	868186
----------------	--------

Gantner Instruments

Austria | Germany | France | Sweden | India | USA | China | Singapore
Montafonerstraße 4 · A-6780 Schruns · T +43 55 56 · 77 463-0

office@gantner-instruments.com
www.gantner-instruments.com