

# ADAM-3112 ADAM-3114

Isolated AC Voltage Input Module

Isolated AC Current Input Module



ADAM-3112

CE FCC

FM APPROVED

## Specifications

### Voltage Input

Full Range Mode		400 V	250 V	120 V
Input Voltage	AC (VRMS)	0 ~ 400	0 ~ 250	0 ~ 120
	DC (V)	0 ~ 400	0 ~ 250	0 ~ 120
Input Impedance		48 k	30 k	14.4 k

### Voltage Output

- Output Signal 0 ~ 5 V<sub>DC</sub>
- Accuracy <±1.0 % for full range
- Output Impedance < 10 Ω @ operating frequency <60 Hz
- Load > 10 kΩ
- Ripple < 120 mVp-p
- Temperature Coefficient 400 ppm/°C
- Input Bandwidth 6 kHz

### Power Consumption

- Supply Voltage 24 V<sub>DC</sub> ± 10%
- Current Consumption 40 mA

### General

- Isolation Protection 1,000 V<sub>DC</sub> (output to power)  
2,500 V<sub>RMS</sub> (input to output, input to power)
- Dimensions (W x H x D) 23.2 x 101 x 93.5 mm (0.91" x 3.97" x 3.68")
- Operating Temperature 0 ~ 60 °C (32 ~ 140 °F)
- Storage Temperature -20 ~ 70 °C (-4 ~ 158 °F)
- Storage Humidity 5 ~ 95%

## Ordering Information

- ADAM-3112-AE Isolated AC voltage input module



ADAM-3114

CE FCC

FM APPROVED

## Specifications

### Current Input

- AC Current Input 0 ~ 5 A<sub>RMSS</sub>
- DC Current Input 0 ~ 5 A

### Voltage Output

- Output Signal 0 ~ 5 V<sub>DC</sub>
- Accuracy <±1.0 % for full range
- Output Impedance <10 Ω @ operating frequency <60 Hz
- Load > 10 kΩ
- Ripple < 120 mVp-p
- Temperature Coefficient 400 ppm/°C
- Input Bandwidth 10 kHz

### Power Consumption

- Supply Voltage 24 V<sub>DC</sub> ± 10%
- Current Consumption 40 mA

### General

- Isolation Protection 1,000 V<sub>DC</sub> (output to power)  
2,500 V<sub>RMS</sub> (input to output, input to power)
- Dimensions (W x H x D) 23.2 x 101 x 93.5 mm (0.91" x 3.97" x 3.68")
- Operating Temperature 0 ~ 60 °C (32 ~ 140 °F)
- Storage Temperature -20 ~ 70 °C (-4 ~ 158 °F)
- Storage Humidity 5 ~ 95%

## Ordering Information

- ADAM-3114-AE Isolated AC current input module