



**2D imager with adjustable stand**

Mounted on the wall, placed on a desk or adjusted angle with fixed position for hands-free scanning.



# MS339

## Affordable rugged 2D imager

**The Unitech MS339 is designed to meet barcode scanning needs at an affordable price.**

Supporting all common 1D and 2D barcodes, this high performance scanner is able to read poorly printed barcodes, reads damaged labels and reads digital barcodes from mobile displays (including QR codes) from various types of displays to enhance service levels.

The soft white auxiliary lighting and green aimer deliver comfortable and convenient scanning experience. The stylish and ergonomic design makes the MS339 fit comfortably in any hand, reducing fatigue during long-time scanning tasks.

**The MS339 comes all-in-one package including 5 years warranty!**

The MS339 is a great fit for a variety of retail and business environments. Its easy plug-and-play set up ensures an easy introduction into your unique workflow.

### Features

- The MS339 comes with coiled 2.4m USB-cable, hands-free stand and 5 years direct replacement warranty.
- Snappy performance
- Adjustable stand design - Desk mount, wall mount or adjustable hands-free scanning position.
- Supports USB/HID, USB/SPP, RS232 and OPOS
- Reads poorly printed barcode and from mobile screens
- Ergonomic design and comfortable grip
- Supports Trigger and Auto-sensing mode
- Durable design: 2.0 Meter drop test and IP52-rated



# v1.1 MS339 Specifications

## Operational & Performance

Receiving Device	Imager sensor, 1280 x 800 pixels
Scan Skew	± 70°
Scan Pitch	± 75°
Scan Roll	360°
Immunity:	100.000 lux
Light Source	Illumination: 5000K, white LED. Aiming: 525 nm peak wavelength, green LED.
Field of view	Horizontal 41° / Vertical 28°
Indicator	Beep, LED
Interface	USB/HID, USB/SPP, RS232 and OPOS* (additional software driver needed)

## Reading distance (DOF)

Depth of Field\*  
1D: 0mm to 340mm

5mil Code39 (3 chars):	5 - 115
10mil Code39 (3 chars):	0 - 250
13mil UPC (6 chars):	15 - 340
20mil Code39 (5 chars):	15 - 340
6.7mil PDF417 (20 chars):	10 - 100
10mil QR (20 chars):	0 - 155
10mil DM (20 chars):	0 - 160
20mil QR (20 chars):	0 - 270

2D: 0mm to 340m

\* = depends on width of barcode

## Symbologies

**1D:** UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128, ISBT 128, Code 93, Code 11 (USD-8), MSI/Plessey, UK/Plessey, China Post, China Finance, Telepen, GS1 DataBar (formerly RSS) variants and TLC-39 postal code.

## Unitech Europe

Tilburg, The Netherlands  
 • Tel.: +31 (0)13 460 9292  
 • Email: [Info@eu.ute.com](mailto:Info@eu.ute.com)  
 • Website: <http://eu.ute.com>



Unitech America

Unitech Asia Pacific

Unitech China

Unitech Europe

Unitech Japan

Unitech Taiwan

\* Warranty: Unitech reserves the right to call back the defect units at her discrete sole decision if Unitech may find it necessarily. Upon the calling, the returning shipping cost will be borne by Unitech except tax and duty if any. Unitech has full decision to stop the warranty coverage before expiration if the defect is found due to abused, sabotage, and/or caused by the acts of God Specifications subject to change without notice.

Copyright 2011 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.

## 2D:

PDF417, QR Code, Data Matrix, Han Xin, Code, Aztec Code, MicroQR Code, MicroPDF417.

## Power Source

Operation Voltage: 5 VDC ± 0.25 V  
 Power consumption: Standby: 1600 mA  
 Working: 300 mA

## Material

Case material: PC + TPU  
 Exit window material: Tempered glass

## Enclosure

Scanner dimension: 90mm x 62.8mm x 153mm  
 Scanner weight: 132g (without cable)  
 Cable: 2.4m coiled cable

## Environmental

Mechanical Shock: Withstands multiple 2.0m drops to concrete.  
 IP Rating: IP52  
 Operating Temperature: -10°C to 50°C  
 Storage Temperature: -20°C to 70°C  
 Relative Humidity: 5% to 90% non-condensing

## Operation modes

Trigger, auto-sensing

## Connectivity

USB cable

## Safety & EMC

Photobiological Safety: EN62471  
 EMC: EN55032  
 ESD Protection: EN61000-4-2  
 RF Immunity: IEC61000-4-3, 10 V/m

## Regulator approvals

CE, FCC

## Warranty

5 Years scanner only\*  
 1 Year USB cable

**unitech**  
because we care