

MicroTouch **ALL-IN-ONE SERIES**

Windows OS joins the all-in-one touch family. 15.6" and 21.5" available for Windows and Android.

Available in sizes 10.1" to 21.5" and supporting both Android and Widows OS, our All-in-One Series offers smooth and effortless performance in a wide variety of applications. With the power to run operating systems from Windows 7 to Windows 10, the All-in-One series is optimized for versatility.

Solutions:



Fitness

Cycling/rowing fitness equipment, Point-of-information and Self check-in/check-out



Hospitality

Self check-in/checkout, Self-service ticketing, Point-of-information



Healthcare

Medical/diagnostic carts, Nursing station,Clinical review



Retail

Self service, Self checkout, Point-of-information, Point-of-sale

MicroTouch ALL-IN-ONE SERIES



IC-156P-AW1-W10 Windows

| Size | 15.6" TFT LCD |
|--------------------|-------------------------------------|
| Processor | Celeron® J1900 (2.0 GHz, 2M Cache) |
| Maximum Resolution | 1920 x 1080 |
| Contrast Ratio | 1000:1 |
| Aspect Ratio | 16:9 |
| Brightness | 450nits (No Touch), 405nits (P-CAP) |
| View Angle | H:178°, V:178° |
| Video Port | 1 x VGA |
| Warranty | 3 year |

See Full Specs



IC-156P-AW2-W10 Windows

| Size | 15.6" TFT LCD |
|--------------------|---------------------------------------|
| Processor | Core i5 7300U (2.60 GHz, 3M Cache) |
| Maximum Resolution | 1920 x 1080 |
| Contrast Ratio | 1000:1 |
| Aspect Ratio | 16:9 |
| Brightness | 450 nits (No Touch), 405 nits (P-CAP) |
| View Angle | H:178°, V:178° |
| Video Port | 1 x Mini DP |
| Warranty | 3 year |

See Full Specs



IC-156P-AW3-W10 Windows

| Size | 15.6" TFT LCD |
|--------------------|---------------------------------------|
| Processor | Core i3 7100U (2.40 GHz, 3M Cache) |
| Maximum Resolution | 1920 x 1080 |
| Contrast Ratio | 1000:1 |
| Aspect Ratio | 16:9 |
| Brightness | 450 nits (No Touch), 405 nits (P-CAP) |
| View Angle | H:178°, V:178° |
| Video Port | 1 x Mini DP |
| Warranty | 3 year |
| | |

See Full Specs



IC-156P-AW4-W10 Windows

| Size | 15.6" TFT LCD |
|--------------------|---------------------------------------|
| Processor | Celeron® 3965U (2.2 GHz, 2M Cache) |
| Maximum Resolution | 1920 x 1080 |
| Contrast Ratio | 1000:1 |
| Aspect Ratio | 16:9 |
| Brightness | 450 nits (No Touch), 405 nits (P-CAP) |
| View Angle | H:178°, V:178° |
| Video Port | 1 x Mini DP |
| Warranty | 3 year |

See Full Specs

MicroTouch ALL-IN-ONE SERIES



IC-215P-AW1-W10 Windows

| Size | 21.5" TFT LCD |
|--------------------|---------------------------------------|
| Processor | Celeron® J1900 (2.0 GHz, 2M Cache) |
| Maximum Resolution | 1920 x 1080 |
| Contrast Ratio | 1000:1 |
| Aspect Ratio | 16:9 |
| Brightness | 250 nits (No Touch), 225 nits (P-CAP) |
| View Angle | H:178°, V:178° |
| Video Port | 1 x VGA |
| Warranty | 3 year |
| | |

See Full Specs



IC-215P-AW2-W10 Windows

| 21.5" TFT LCD |
|---------------------------------------|
| Core™ i5-7300U (2.60 Gz, 3M Cache) |
| 1920 x 1080 |
| 1000:1 |
| 16:9 |
| 250 nits (No Touch), 225 nits (P-CAP) |
| H:178°, V:178° |
| 1 x Mini DP |
| 3 year |
| |

See Full Specs



IC-215P-AW3-W10 Windows

| Size | 21.5" TFT LCD |
|--------------------|---------------------------------------|
| Processor | Core™ i3-7100U |
| | (3MB Cache, up to 2.4GHz) |
| Maximum Resolution | 1920 x 1080 |
| Contrast Ratio | 3000:1 |
| Aspect Ratio | 16:9 |
| Brightness | 250 nits (no touch), 212 nits (P-CAP) |
| View Angle | H:178°, V:178° |
| Video Port | 1 x Mini DP/ USB 3.1 Type-C Display |
| | Alt Mode |
| Warranty | 3 year |

See Full Specs



IC-215P-AW4-W10 Windows

| Size | 21.5" TFT LCD |
|--------------------|---------------------------------------|
| Processor | Celeron® 3965U (2.20 GHz, 2M Cache) |
| Maximum Resolution | 1920 x 1080 |
| Contrast Ratio | 1000:1 |
| Aspect Ratio | 16:9 |
| Brightness | 250 nits (No Touch), 225 nits (P-CAP) |
| View Angle | H:178°, V:178° |
| Video Port | 1 x Mini DP |
| Warranty | 3 year |
| | |

See Full Specs

MicroTouch ALL-IN-ONE SERIES



IC-215P-AA2 android

| Size | 21.5 " TFT LCD |
|--------------------|--|
| Processor | Rockchip RK-3399, Dual-core Cortex-A72 up to 1.8GHz, Quad-core Cortex-A53 up to 1.4GHz |
| Maximum Resolution | 1920 x 1080 |
| Contrast Ratio | 1000:1 |
| Aspect Ratio | 16:9 |
| Brightness | 250 nits (No Touch), 225 nits (P-CAP) |
| View Angle | H:178°, V:178° |
| Video Port | 1 x HDMI, 1 x 3.0 Type A, 1 x 3.0 USB Type C (OTG support) |
| Warranty | 3 year |
| | |

See Full Specs



IC-156P-AA2 android

| IO IOOI AAL | anarola |
|--------------------|---|
| Size | 15.6 " TFT LCD |
| Processor | Rockchip RK-3399, Dual-core Cortex-A72 up to 1.8GHz, Quad-core Cortex-A53 |
| | up to 1.4GHz |
| Maximum Resolution | 1920 x 1080 |
| Contrast Ratio | 1000:1 |
| Aspect Ratio | 16:9 |
| Brightness | 450 nits (No Touch), 405 nits (P-CAP) |
| View Angle | H:178°, V:178° |
| Video Port | 1 x HDMI (1080p 60Hz support), 1 x USB 3.0 |
| | Type A, 1 x USB 3.0 Type C (OTG support), |
| | 1 x Micro SD Slot (SDHC 2.0 support) |
| Warranty | 3 year |

See Full Specs



IC-100P-AA1 android

| up to 1.8GHz Maximum Resolution 1280 x 800 Contrast Ratio 1000:1 Aspect Ratio 16:10 Brightness 450 nits (No Touch), 382 nits (P-CAP) View Angle H:160°, V:160° Video Port 1 x HDMI Type-C (Mini HDMI), 1 x USB 2.0 | 10 1001 701 | |
|---|--------------------|---|
| up to 1.8GHz Maximum Resolution 1280 x 800 Contrast Ratio 1000:1 Aspect Ratio 16:10 Brightness 450 nits (No Touch), 382 nits (P-CAP) View Angle H:160°, V:160° Video Port 1x HDMI Type-C (Mini HDMI), 1 x USB 2.0 Type A, 1 x USB 2.0 Type C (OTG support 1 x RJ45 Giga LAN, PoE (Power Over Ethernet) 48V/56V support | Size | 10.1 " TFT LCD |
| Contrast Ratio 1000:1 Aspect Ratio 16:10 Brightness 450 nits (No Touch), 382 nits (P-CAP) View Angle H:160°, V:160° Video Port 1 x HDMI Type-C (Mini HDMI), 1 x USB 2.0 Type A, 1 x USB 2.0 Type C (OTG support 1 x RJ45 Giga LAN, PoE (Power Over Ethernet) 48V/56V support | Processor | Rockchip RK-3288, Quad-core Cortex-A17 up to 1.8GHz |
| Aspect Ratio Brightness 450 nits (No Touch), 382 nits (P-CAP) View Angle H:160°, V:160° Video Port 1 x HDMI Type-C (Mini HDMI), 1 x USB 2.0 Type A, 1 x USB 2.0 Type C (OTG support 1 x RJ45 Giga LAN, PoE (Power Over Ethernet) 48V/56V support | Maximum Resolution | 1280 x 800 |
| Brightness 450 nits (No Touch), 382 nits (P-CAP) View Angle H:160°, V:160° Video Port 1x HDMI Type-C (Mini HDMI), 1x USB 2.0 Type A, 1x USB 2.0 Type C (OTG support 1x RJ45 Giga LAN, PoE (Power Over Ethernet) 48V/56V support | Contrast Ratio | 1000:1 |
| View Angle H:160°, V:160° Video Port 1 x HDMI Type-C (Mini HDMI), 1 x USB 2.0 Type A, 1 x USB 2.0 Type C (OTG support 1 x RJ45 Giga LAN, PoE (Power Over Ethernet) 48V/56V support | Aspect Ratio | 16:10 |
| Video Port 1 x HDMI Type-C (Mini HDMI), 1 x USB 2.0 Type A, 1 x USB 2.0 Type C (OTG support 1 x RJ45 Giga LAN, PoE (Power Over Ethernet) 48V/56V support | Brightness | 450 nits (No Touch), 382 nits (P-CAP) |
| Type A, 1 x USB 2.0 Type C (OTG support 1 x RJ45 Giga LAN, PoE (Power Over Ethernet) 48V/56V support | View Angle | H:160°, V:160° |
| Warranty 3 year | Video Port | Type A, 1 x USB 2.0 Type C (OTG support), 1 x RJ45 Giga LAN, PoE (Power Over |
| | Warranty | 3 year |

See Full Specs



www.MicroTouch.com | us.orders@microtouch.com

TES America, LLC | 215 Central Avenue, Holland, MI 49423 | (616) 786-5353